

Industrial Foggers

INDUSTRIAL FOGGERS

Seamless, rotationally molded for maximum strength and lifelong durability. Made of corrosion resistant materials for use with many chemicals. 1.5 Gal. capacity with 3-1/2" wide tank opening for easy filling and emptying. No need to dissemble unit to fill. Fixed 45° angle. No swivels to wear out. Motors available in both 110V/60Hz or 220/240V. Low profile for maximum stability. Use for flood and fire damage restoration. Can be used in food plants, hotels, barns, parks, schools, restaurants and hospitals. Great to use for controlling odors.

MY-TI-LITE 2300

- » Preset discharge of 9 oz./min.
- » Non-ULV fogger
- » Single stage motor
- » Liquid is discharged as a wet fog that settles quickly
- » Serves the need for a wide range of uses both indoor and outdoor
- » Handles both water-based and oil-based liquids



ULTRA-LITE 2400

- » Adjustable flow from 0-9 oz./min.
- » Heavy-duty motor for reliability
- » Handles both water-based and oil-based liquids
- » Set the valve to a flow flow rate to produce near invisible ULV droplets
- » Heavier fogs and mists will increase the flow rate

| ORDER# | MODEL# | DESCRIPTION |
|----------|--------|-------------------|
| 15015100 | 2400 | Ultro-Lite Fogger |

FLEX-A-LITE 2600

- » Variable flow from ULV to light mist
- » Adjustable flow from 0-18 oz./min.
- » 2-stage motor
- » Nozzle mounted on 18" hose, longer hoses available (36" or 48")
- » Handles both water-based and oil-based liquids, this one machine can handle all your fogger needs

| ORDER# | MODEL# | DESCRIPTION |
|----------|--------|--------------------|
| 15014901 | 2600 | Flex-A-Lite Fogger |











