



Report Number: 2132

ULTRABOND 2132

Multi-Purpose Medium Viscosity Epoxy Coating & Bonding System- 100% Epoxy

Ultrabond 2132 is a GREY, two-component, 100% solids, high strength epoxy coating and bonding adhesive. It is a solvent free, self leveling, non-blushing, medium viscosity epoxy system. **Ultrabond 2132** is ideal for use in temperatures ranging from 60°F - 90°F.

“Ultrabond 2132” is the ideal product for coating laboratory, warehouse, garage, aircraft hangars, food processing plants and automotive repair floors.

FEATURES:

- High Strength Epoxy Adhesive.
- Non-Blushing Coating System
- Self Leveling Medium Viscosity
- Easy to use 1:1 Ratio System.
- Moisture Insensitive Epoxy.
- Excellent Stain & Chemical Resistance

APPLICATIONS INCLUDE:

- Coating Warehouse, Laboratory, Garage, Warehouse and Office Floors
- EPA Registered Ingredients.
- Bonding Fresh Concrete to Hardened Concrete
- Mortar Repair Material (when mixed with silica sand)
- Self-Leveling Spall and Patching Material

Available in 2-Gallon Kits Coverage 128 sq ft. per Kit

Gel Time: 37 Minutes

Pot Life: 15-20 Minutes

Tack-Free Time: Approx 8 hours Traffic Time (foot traffic): 24 Hours



T
E
C
H
N
I
C
A
L

R
E
P
O
R
T