

## ΤΙΤΔΠ 100

## **Specifications**

*itan 100* air sanitation offers an additional level of protection by helping to keep the air healthier and cleaner within your; Offices, Break Rooms, Workstations, Fulfillment and Distribution Centers.

**TITAN 100** the Next Generation of the Airocide GCS-100 Model.

## Airocide ΤΙΤΔΠ 100:

- NASA developed technology, engineered for broad applications across almost any industry
- Uses a Photocataytic Reactor and Kills, Airborne Bacteria, Mold/Fungi, Viruses, and Mycotoxins
- Listed FDA Class II Medical Device
- Completely user and environmentally safe, NO EMISSIONS - NO TOXIC GASES / CHEMICALS
- Extremely energy efficient and low operational cost, consuming less Energy then (4) 100 watt light bulbs.
- Easy to Install and Operates
   24/7 in most all environments



Construction

Aluminum and Stainless Steel

Electrical

120 VAC, 4 amp 9 ft Power Cord (supplied with unit)

Controls

On/Off switch

## Maintenance

The Airocide technology has been designed and engineered for extremely low operational/maintenance cost. Each unit utilizes less than 4 amps with a power consumption of 390 watts. The proprietary high intensity energy PCO lamps only require annual replacement. The 4" protection filter should be replaced approximately every 6 months\*. Lamp kit and protective filter replacement orders can be placed with SteriLumen, or an authorized Airocide distributor.

\*NOTE: Depending on the particular dust load in a given environment, the filter may need to be changed more frequently.

Power Cord Length (Custom Lengths Available)	9 ft.
Power (Pre-Set / Non-Switchable)	120 Volt / 220 Volt
Recommended Available Amps Power Consumption In Watts	4 Amps / 2 Amp 390 Watts / 195 Watts
Warranty	5 Years

Unit Dimensions	39" x 22" x 14 3/8"
	(.991 M x .559 M x .365 M)
Unit Dimensions With	45 1/2" x 29" x 19"
Shipping Box	(1.16 M x .737 M x 483 M)
Unit Weight	70 lbs
	(31.75 KG)
Shipping Weight (Excluding Pallet Weight If Used)	78 lbs
	(35.38 KG)





